Safety data sheet According to UK REACH (S.I. 2019/758)

SETA-0114-0017 - FIJI Calibration Material Set ASTM D7797





SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: SETA-0114-0017 - FIJI Calibration Material Set ASTM D7797

Kerosine (petroleum), sweetened

CAS: 91770-15-9

REACH:

Other means of identification:

Not relevant

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses (Professional users): Chemical sample for use in laboratories Relevant uses (Industrial user): Chemical sample for use in laboratories Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Stanhope-Seta London street

KT16 8AP Chertsey - United Kingdom

Phone: +44 (0)1932 564391 - Fax: +44 (0)1932 568363

service@stanhope-seta.co.uk https://www.stanhope-seta.co.uk/

1.4 Emergency telephone number: +44 (0)1932 564391

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Classification of this product has been carried out in accordance with GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567).

Asp. Tox. 1: Aspiration hazard, Category 1, H304 Flam. Liq. 3: Flammable liquids, Category 3, H226 Repr. 2: Reproductive toxicity, Category 2, H361d

2.2 Label elements:

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Danger





Hazard statements:

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Repr. 2: H361d - Suspected of damaging the unborn child.

Precautionary statements:

P201: Obtain special instructions before use.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P370+P378: In case of fire: Use Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC) to extinguish.

P403+P235: Store in a well-ventilated place. Keep cool.

P501: Dispose of the contents and/or its container in line with regulations on dangerous waste or packaging and waste packaging respectively.

Substances that contribute to the classification

Kerosine (petroleum), sweetened (CAS: 91770-15-9); Toluene (CAS: 108-88-3)

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

- CONTINUED ON NEXT PAGE -

Safety data sheet According to UK REACH (S.I. 2019/758)

SETA-0114-0017 - FIJI Calibration Material Set ASTM D7797





SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Chemical description: Organic compounds

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

| | Identification | Chemical name/Classification | Concentration |
|-----------------------|--|--|---------------|
| CAS: EC: REACH: | 91770-15-9 294-799-5 01-2119502385-46- XXXX | Kerosine (petroleum), sweetened Asp. Tox. 1: H304 - Danger | 75 - <100 % |
| CAS: EC: REACH: | 108-88-3 203-625-9 01-2119471310-51- XXXX | Toluene Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger | 2.5 - <10 % |

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

3.2 Mixture:

Not relevant

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the affected person from the area of exposure, provide them with fresh air, and keep them at rest. In severe cases such as cardiorespiratory arrest, administer artificial respiration techniques if properly trained (CPR, oxygen provision, etc.) and seek immediate medical assistance.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

Date of compilation: 2024-03-28 Revised: 2025-10-20 Version: 4 (Replaced 3) **Page 2/11**

Safety data sheet According to UK REACH (S.I. 2019/758)

SETA-0114-0017 - FIJI Calibration Material Set ASTM D7797





SECTION 5: FIREFIGHTING MEASURES (continued)

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in The Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres Regulations 2016 and with the minimum requirements for protecting the security and health of workers under the selection criteria of The Dangerous Substances and Explosive Atmospheres Regulations 2002, 2002 No. 2776. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Date of compilation: 2024-03-28 Revised: 2025-10-20 Version: 4 (Replaced 3) Page 3/11

Safety data sheet According to UK REACH (S.I. 2019/758)

SETA-0114-0017 - FIJI Calibration Material Set ASTM D7797





SECTION 7: HANDLING AND STORAGE (continued)

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 **Control parameters:**

Substances whose occupational exposure limits have to be assessed in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

| Identification | Occup | Occupational exposure limits | | |
|----------------|--------------|------------------------------|-----------------------|--|
| Toluene (1) | WEL (8h) | 50 ppm | 191 mg/m ³ | |
| CAS: 108-88-3 | WEL (15 min) | 100 ppm | 384 mg/m ³ | |

(1) Skin

DNEL (Workers):

| | | Short exposure | | Long exposure | |
|----------------|------------|-----------------------|-----------------------|-----------------------|-----------------------|
| Identification | | Systemic | Local | Systemic | Local |
| Toluene | Oral | Not relevant | Not relevant | Not relevant | Not relevant |
| CAS: 108-88-3 | Dermal | Not relevant | Not relevant | 384 mg/kg | Not relevant |
| EC: 203-625-9 | Inhalation | 384 mg/m ³ | 384 mg/m ³ | 192 mg/m ³ | 192 mg/m ³ |

DNEL (General population):

| | | Short e | xposure | Long ex | xposure |
|----------------|------------|-----------------------|-----------------------|------------------------|------------------------|
| Identification | | Systemic | Local | Systemic | Local |
| Toluene | Oral | Not relevant | Not relevant | 8.13 mg/kg | Not relevant |
| CAS: 108-88-3 | Dermal | Not relevant | Not relevant | 226 mg/kg | Not relevant |
| EC: 203-625-9 | Inhalation | 226 mg/m ³ | 226 mg/m ³ | 56.5 mg/m ³ | 56.5 mg/m ³ |

PNEC:

| Identification | | | | |
|----------------|--------------|--------------|-------------------------|-------------|
| Toluene | STP | 13.61 mg/L | Fresh water | 0.68 mg/L |
| CAS: 108-88-3 | Soil | 2.89 mg/kg | Marine water | 0.68 mg/L |
| EC: 203-625-9 | Intermittent | 0.68 mg/L | Sediment (Fresh water) | 16.39 mg/kg |
| | Oral | Not relevant | Sediment (Marine water) | 16.39 mg/kg |

8.2 **Exposure controls:**

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding << UKCA marking>> or <<CE marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Safety data sheet According to UK REACH (S.I. 2019/758)

SETA-0114-0017 - FIJI Calibration Material Set ASTM D7797





SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Pictogram | PPE | Remarks |
|--|---|--|
| Mandatory respiratory tract protection | Filter mask for gases and vapours (Filter type: A) | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. |

C.- Specific protection for the hands

| Pictogram | PPE | Remarks |
|---------------------------|--|--|
| Mandatory hand protection | Chemical protective gloves (Material: Linear low -density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm) | Replace the gloves at any sign of deterioration. |

D.- Eye and face protection

| Pictogram | PPE | Remarks |
|---------------------------|-------------|--|
| Mandatory face protection | Face shield | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection

| Pictogram | PPE | Remarks |
|------------------------------------|---|---|
| Mandatory complete body protection | Disposable clothing for protection against chemical risks, with antistatic and fireproof properties | For professional use only. Clean periodically according to the manufacturer's instructions. |
| Mandatory foot protection | Safety footwear for protection against chemical risk, with antistatic and heat resistant properties | |

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

| Emergency measure | Standards | Emergency measure | Standards |
|-------------------|---|-------------------|--|
| 1 | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 | - ∰ | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |
| Emergency shower | | Eyewash stations | |

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:

V.O.C. (Supply): 99.99 % weight

V.O.C. density at 20 °C: 802.25 kg/m³ (802.25 g/L)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liquid

*Not relevant due to the nature of the product, not providing information property of its hazards.

Revised: 2025-10-20 Date of compilation: 2024-03-28 Version: 4 (Replaced 3) Page 5/11

Safety data sheet According to UK REACH (S.I. 2019/758)

SETA-0114-0017 - FIJI Calibration Material Set ASTM D7797





SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Appearance: Colourless
Colour: Not relevant *
Odour: Aromatic
Odour threshold: Not relevant *

Volatility:

Boiling point at atmospheric pressure: 202 °C Vapour pressure at 20 °C: 548 Pa

Vapour pressure at 50 °C: 2302.08 Pa (2.3 kPa)

Evaporation rate at 20 °C: Not relevant *

Product description:

Density at 20 °C: 802.3 kg/m³ Relative density at 20 °C: 0.802

Dynamic viscosity at 20 °C: Not relevant * Kinematic viscosity at 20 °C: Not relevant * Kinematic viscosity at 40 °C: <20.5 mm²/s Concentration: Not relevant * pH: Not relevant * Vapour density at 20 °C: Not relevant * Partition coefficient n-octanol/water 20 °C: Not relevant * Solubility in water at 20 °C: Not relevant * Solubility properties: Not relevant * Not relevant * Decomposition temperature: Melting point/freezing point: Not relevant *

Flammability:

Flash Point: >30 °C (ISO 3679)
Flammability (solid, gas): Not relevant *
Autoignition temperature: 250 °C
Lower flammability limit: Not relevant *
Upper flammability limit: Not relevant *

Particle characteristics:

Median equivalent diameter: Not relevant *

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Not relevant *

Corrosive to metals:

Heat of combustion:

Aerosols-total percentage (by mass) of flammable

Not relevant *

Not relevant *

components: Other safety characteristics:

Surface tension at 20 °C:

Refraction index:

Not relevant *

 ${}^*\mathrm{Not}$ relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

Date of compilation: 2024-03-28 Revised: 2025-10-20 Version: 4 (Replaced 3) **Page 6/11**

Safety data sheet According to UK REACH (S.I. 2019/758)

SETA-0114-0017 - FIJI Calibration Material Set ASTM D7797





SECTION 10: STABILITY AND REACTIVITY (continued)

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable | Not applicable | Risk of combustion | Avoid direct impact | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3. IARC: Toluene (3)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Suspected to damage the foetus
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Safety data sheet According to UK REACH (S.I. 2019/758)

SETA-0114-0017 - FIJI Calibration Material Set ASTM D7797



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

May be fatal if swallowed and enters airways.

Other information:

Not relevant

Specific toxicology information on the substances:

| Identification | Acute | toxicity | Genus |
|---------------------------------|------------------------|-----------------|-------|
| Toluene | LD50 oral | 5580 mg/kg | Rat |
| FC: 203-625-9 | LD50 dermal | 12124 mg/kg | Rat |
| | LC50 inhalation vapour | 28.1 mg/L (4 h) | Rat |
| Kerosine (petroleum), sweetened | LD50 oral | >5000 mg/kg | Rat |
| FC: 294-799-5 | LD50 dermal | | |
| | LC50 inhalation | | |

SECTION 12: ECOLOGICAL INFORMATION

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Toxicity:

Acute toxicity:

| Identification | | Concentration | Species | Genus |
|----------------|------|------------------|----------------------|------------|
| Toluene | LC50 | 5.5 mg/L (96 h) | Oncorhynchus kisutch | Fish |
| CAS: 108-88-3 | | 3.78 mg/L (48 h) | Ceriodaphnia dubia | Crustacean |
| | EC50 | Not relevant | | |

12.2 Persistence and degradability:

Substance-specific information:

| Identification | Degradability | | Biodegradability | |
|----------------|---------------|--------------|------------------|----------|
| Toluene | BOD5 | 2.5 g O2/g | Concentration | 100 mg/L |
| CAS: 108-88-3 | COD | Not relevant | Period | 14 days |
| EC: 203-625-9 | BOD5/COD | Not relevant | % Biodegradable | 100 % |

12.3 Bioaccumulative potential:

Substance-specific information:

| Identification | Bioaccumulation potential | | |
|----------------|---------------------------|----------|--|
| Toluene | BCF | 90 | |
| CAS: 108-88-3 | Pow Log | 2.73 | |
| EC: 203-625-9 | Potential | Moderate | |

12.4 Mobility in soil:

| Identification | Absorption/desorption | | Volatility | |
|----------------|-----------------------|----------------------|------------|-----------------|
| Toluene | Koc | 178 | Henry | 672.8 Pa·m³/mol |
| CAS: 108-88-3 | Conclusion | Moderate | Dry soil | Yes |
| | Surface tension | 2.793E-2 N/m (25 °C) | Moist soil | Yes |

Safety data sheet According to UK REACH (S.I. 2019/758)

SETA-0114-0017 - FIJI Calibration Material Set ASTM D7797





SECTION 12: ECOLOGICAL INFORMATION (continued)

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| | Code | Description | Waste class |
|---|-----------|--|-------------|
| ĺ | 16 03 05* | organic wastes containing hazardous substances | Hazardous |

Type of waste:

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable, HP10 Toxic for reproduction

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste (England & Wales) Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2025 and RID 2025:



14.1 UN number: UN1993

14.2 UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Toluene; Kerosine (petroleum),

sweetened)

14.3 Transport hazard class(es): Labels: 3

14.4 Packing group: III 14.5 Environmental hazards: Nο

14.6 Special precautions for user

D/E Tunnel restriction code:

Physico-Chemical properties: see section 9

Limited quantities: 5 I

14.7 Transport in bulk according to Annex II of Marpol and

the IBC Code:

Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 42-24:

- CONTINUED ON NEXT PAGE -

Safety data sheet According to UK REACH (S.I. 2019/758)



SETA-0114-0017 - FIJI Calibration Material Set ASTM D7797





SECTION 14: TRANSPORT INFORMATION (continued)

14.1 UN number: UN1993

14.2 UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Toluene; Kerosine (petroleum),

sweetened)

14.3 Transport hazard class(es): 3

Labels: 3
Packing group: II

14.4Packing group:III14.5Marine pollutant:No

14.6 Special precautions for user

Special regulations: 274, 223, 955 EmS Codes: F-E, S-E Physico-Chemical properties: see section 9

Limited quantities: 5 L

Segregation group: Not relevant **Transport in bulk according** Not relevant

14.7 Transport in bulk according to Annex II of Marpol and

the IBC Code:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2025:



14.1 UN number: UN1993

14.2 UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Toluene; Kerosine (petroleum),

sweetened)

14.3 Transport hazard class(es): 3

Labels: 3 **14.4 Packing group:** III

14.6 Special precautions for user

14.5 Environmental hazards:

Physico-Chemical properties: see section 9

14.7 Transport in bulk according to Annex II of Marpol and

the IBC Code:

Not relevant

No

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Not relevant
- Substances listed in UK REACH Authorisation List (Annex 14): Not relevant

The Control of Major Accident Hazards Regulations 2015:

| Section | Description | Lower-tier requirements | Upper-tier requirements |
|---------|-------------------|-------------------------|-------------------------|
| P5c | FLAMMABLE LIQUIDS | 5000 | 50000 |

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Contains more than 0.1 % of Toluene by weight. Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Date of compilation: 2024-03-28 Revised: 2025-10-20 Version: 4 (Replaced 3) **Page 10/11**

Safety data sheet According to UK REACH (S.I. 2019/758)

SETA-0114-0017 - FIJI Calibration Material Set ASTM D7797





SECTION 15: REGULATORY INFORMATION (continued)

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Texts of the legislative phrases mentioned in section 2:

H361d: Suspected of damaging the unborn child.

H304: May be fatal if swallowed and enters airways.

H226: Flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Repr. 2: H361d - Suspected of damaging the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50

LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET
Date of compilation: 2024-03-28 Revised: 2025-10-20 Version: 4 (Replaced 3) Page 11/11